



ISO 9001:2000 Certificate No.: CH98/8032

ISO 14001:2004 Certificate No.: CH03/0112

OHSAS 18001:1999 Certificate No.: CH05/0675

## Address:

No. 3, Taban St., Valie – e – Asr St., Tehran - Iran

Tel:

(+98 21)82122700

Fax:

(+98 21)8867 4126-27

Web-site:

www.arpc-ir.net

E-mail:

Sales@arpc-ir.net

No. 3, West Taban St.,

Africa St.,

Tehran - Iran

## Polypropylene homo-polymer

## Moplen HP550J

Typical properties	Test method (ASTM)	Unit	Value
MFR @230°C, 2.16 kg	D1238/L	gr/10min	3.2
Flexural Modulus	D790	MPa	1550
Notched Izod Impact@23°C	D256	J/m	55
Tensile Strength@Yield	D638	MPa	35
Elongation@Yield	D638	%	12
Vicat Softening Point,10N	D1525	°C	156
HDT(0.46N/mm²)	D648	°C	94
Rockwell Hardness	D785	R Scale	102
Oven Aging@150°C	D3012	Hours	360

> Values shown are averages & are not to be considered as product specifications.

## Main application & Characteristics:

Moplen HP550J is a polypropylene homo-polymer particularly suitable for the extrusion of sheet for thermoforming, film yarn & monofilament. Moplen HP550J combines outstanding processability with good mechanical properties.

Moplen HP550J is designed to produce stiff sheet for high quality thermoforming such as vending cups, packaging for dairy products & trays for fruit, biscuits & chocolates.

Moplen HP550J is also particularly suitable to produce film yarn, with both cast & tubular processes .Textile film yarns with a denier count of not more than 1100 to 1200 are used for the production of carpet backings, bags, industrial fabrics, mats & artificial grass .Film yarn with a denier count ranging from 3000 to 28000 is used for baler twines, packaging twines & ropes. Moplen HP550J is also well suited for the production of monofilament used for instance for brush & broom filling & technical applications.

Another typical application of Moplen HP550J is the extrusion of nets for various purposes.

\* Moplen HP550J is suitable for food contact.

Tel:
(+98 21)8867 4127
-
Fax:
(+98 21)8867 4126
\A/
Web-site:
www.arpc-ir.net
F "
E-mail:
Sales@arpc-ir.net