

NAVID ZAR CHIMI Ind. Co. Polypropylene Manufacturer

## Parslen ZH552R

Polypropylene Homopolymer for Production of CF, BCF and Staple Fibers.

## @ Product Description:

- Parslen ZH552R is suitable for low denier staple fibers for nonwoven fabrics, as well as production of continuous filament with medium tenacity and bulk continuous filaments.
- This grade exhibits excellent anti gas fading properties.

## @ Application:

 ZH552R has wide use for production of carpets, upholstery, sportswear, straps, safety belts, diapers and sport bags.



| Typical Properties [a,b]                 | Method      | Unit      | Value(a) | Tolerance |  |
|--|-------------|-----------|----------|-----------|--|
| Melt flow rate(230 ° C, 2.16 Kg)         | ASTM D 1238 | gr/10 min | 25       | ±3        |  |
| Vicat softening point (9.8 N)            | ASTM D 1525 | ° C       | 152      | ±4        |  |
| H.D.T. (0.46 MPa)                        | ASTM D 648  | °C        | 94       | ±8        |  |
| Flexural modulus                         | ASTM D 790  | MPa       | 1500     | ±150      |  |
| Tensile strength at yield                | ASTM D 638  | MPa       | 32       | ±4        |  |
| Elongation at yield                      | ASTM D 638  | %         | 13       | -3        |  |
| Izod impact strength( notched ) at 23° C | ASTM D 256  | J/m       | 30       | ±3        |  |
| Rockwell hardness [R - B Scale]          | ASTM D 785  | R-B       | 100      | +20       |  |

- a) Values shown are averages and are not to be considered as exact product specifications.
- b) All specimens are prepared by injection molding.

(Last revised 31, July 2008)

